

## **MAB 525 / 525 SB**

The compact heavy-duty machine with more motor power and less weight.

## THE STRONG

**COMPACT MACHINES** 

MOTOR STA

Magnetic core drilling machine with two-speed oil bath gearbox. Ideal for the service and maintenance department thanks to just 16 kg. weight. With MT 3 Morse taper system and drilling capacity up to Ø 50 mm. Torsion-resistant design through single-piece gearbox housing with slide.

Overheating protection

Torque control

Full wave control electronics

Clockwise/anticlockwise rotation

Quick-change drilling system

Permanent internal lubrication

Magnet indicator

MAB 525/525 SB			
Motor output	1,600 W		
Voltage	230 V AC, 50 - 60 Hz		
Stroke	160 mm		
Magnet dimensions	84 x 168 x 48 mm		
Weight	16 kg		
Quick-change drilling system	KEYLESS, 19 mm $(^3/_4")$		
Spindle taper	MT 3		
Gear 1 range	70 – 280 rpm		
Gear 2 range	180 – 580 rpm		
Permanent internal lubrication	✓		
Torque control	<b>✓</b>		
Full wave control electronics	<b>✓</b>		
Magnet indicator	<b>✓</b>		
Overheating protection	✓		
Clockwise/anticlockwise rotation	✓		
Carbon brush wear indicator	<b>✓</b>		
MAB 525 230 V	MAB 525 110/125 V		
MAB 525SB 230 V	MAB 525SB 110/125 V		



- 1 Magnetic core drilling machine
- 1 KEYLESS quick-change drilling system 19 mm Weldon (3/4")
- 1 Tapping adapter ZGA 010, ZGA 012, ZGA 016
- 1 Ejector pin ZAK 075, ZAK 100
- 1 Hard-top case
- 1 Safety lashing strap
- 1 Taper drift MT 3/B16
- 1 Gear rim drill chuck 1 13 mm
- 1 Ejector drift MT 3
- 1 Operating instructions

Core drill	Twist drill	Reamer	Countersink	Tapping
HSS Ø 50 mm TCT Ø 60 mm Cutting depth: 30-55-75 mm	Ø 20 mm	Ø 20 mm	Ø 50 mm	M20












Internal cable feed



Cuffesgrange, Co.Kilkenny PH: (056) 7729949 Portlaoise, Co.Laois PH: (057) 8621479

