



## TECHNOLOGY PLASMA 60 XT



NEW

### Overview

#### TECHNOLOGY PLASMA 60 XT

cod. 816148

Inverter, compressed air plasma cutting system, with contact striking of pilot arc.

Allows a rapid, distortion-proof cutting, grid cutting and gauging of all conductive materials such as steel, stainless steel, galvanised steel, aluminium, copper, brass, etc.

Features:

- robust and impact resistant;
- reduced weight and dimensions;
- warning led for torch under voltage, protections;
- warning led for consumables change;
- torch automatic cooling;
- visualization of air pressure;
- thermostatic, overvoltage, undervoltage, overcurrent, air failure protections.

Complete with PH torch.



1 PH 230V



CE MARKING



EAC CERTIFICATION

### Technical data

CODE	CODE 816148	MAX ABSORBED CURRENT	34 A	MAX	MAX CUTTING THICKNESS	20 mm		
V <sub>1PH</sub>	SINGLE PHASE MAINS VOLTAGE	230 V	P <sub>MAX</sub>	MAX ABSORBED POWER	5,5 kW	↓	COMPRESSED AIR CAPACITY	100 L/ min
F	MAINS FREQUENCY	50 / 60 Hz	FUSE	MAINS FUSE	20 A	↓	COMPRESSED AIR PRESSURE	4 - 5 bar
A <sub>MIN</sub> / A <sub>MAX</sub>	CURRENT RANGE	10 - 60 A	η	EFFICIENCY	90 %	IP	PROTECTION DEGREE	IP23



**TECHNOLOGY PLASMA 60 XT**



MAX CURRENT 50A @ 30 % A



POWER FACTOR (cosphi) 0,7



DIMENSIONS 50,6 x 18,2 x 29,2 cm



MAX NO LOAD VOLTAGE 313 V



**KILKENNY WELDING SUPPLIES LTD**

**Cuffesgrange,  
Co. Kilkenny.  
Phone: 056 7729949**

**Timahoe Road,  
Portlaoise, Co. Laois.  
Phone: 057 8621479**

**Email: [info@kws.ie](mailto:info@kws.ie)**