



PTE 28 LCD



Overview

PTE 28 LCD

cod. 824051

Column spot welding machine with movable arms, microprocessor digitally controlled.

The digital, multifunction LCD control panel allows to operate: in EASY mode (setting of spot welding current and time); in EXPERT mode (setting of different spot welding parameters) storing up to 20 customised programmes.

It operates both in continuous and pulse mode and grants optimum results on different kinds of steel.

Features:

- adjustment of spot welding current (%), time (cycles), force of electrodes compression
- choice of various parameters of the spot welding cycle (approach, slope, welding and pause time and pulse number)
- easy to read LCD display
- mechanical pedal control
- gap setting of the arms
- thermal protection with indicator

The model requires water cooling for electrodes and arms.



CE MARKING



EAC CERTIFICATION

Technical data

CODE	CODE 824051	RATED POWER X=50% 25 kVA	PROTECTION DEGREE IP20
DOUBLE PHASE MAINS VOLTAGE 400 V		POWER FACTOR (cosphi) 0,7	DIMENSIONS 79 x 32 x 128 cm
MAINS FREQUENCY 50 / 60 Hz		MAX WELD.THICK. ON 2 SHEETS 5 + 5 mm	WEIGHT 147 kg
MAX SPOT-WELDING CURRENT 16400 A		MAX ELECTRODES POWER 220 daN	EAN CODE 800489797156 8
MAX NO LOAD VOLTAGE 4,2 V		ARMS PROJECTION 330 mm	PIECES/PALLET 3 pz/pallet
MAX ABSORBED POWER 60 kVA		DUTY CYCLE 5,5 %	



PTE 28 LCD

Included Accessories

ARM L=350MM - 443021



STANDARD STRAIGHT ELECTRODE XP - 690035



KILKENNY WELDING SUPPLIES LTD

**Cuffesgrange,
Co. Kilkenny.
Phone: 056 7729949**

**Timahoe Road,
Portlaoise, Co. Laois.
Phone: 057 8621479**

Email: info@kws.ie